

View Online at <https://aerobasegroup.com/nsn/3120-00-922-1756>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

Between 2.3780 inches and 2.4980 inches

Bore Diameter:

Between 0.3745 inches and 0.3750 inches

Lubrication Material:

Grease

Outer Member Outside Diameter:

1.0000 inches

Bore Center To Shank End Distance:

Between 1.8780 inches and 1.9980 inches

Outer Member Width:

Between 0.4010 inches and 0.4110 inches

Inner Member Width:

Between 0.4950 inches and 0.5000 inches

Shank Thread Length:

Between 1.1900 inches and 1.3100 inches

Static Radial Load Rating:

11640 pounds

Thread Diameter:

0.438 inches

Features Provided:

Flush lubrication fitting

Thready Qty Per Inch (tpi):

20

Hardness Rating:

59.0 rockwell c inner member and 63.0 rockwell c inner member

Special Features:

0.0002 in. Min chromium plating thk, 0.0002 in. Cadmium plating thk

Material:

Steel comp e52100 rod end body

Surface Treatment:

Cadmium rod end body

Surface Treatment Specification:

Qq-p-416 type 1 cl 3 federal specification single treatment response rod end body

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0