# NSN 3120-00-922-6097

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-922-6097

# **Overall Length:**

Between 0.1500 inches and 0.1600 inches

## **Body Outside Diameter:**

Between 0.2820 inches and 0.2830 inches

# **Body Inside Diameter:**

Between 0.1900 inches and 0.1910 inches

### Flange Outside Diameter:

Between 0.4280 inches and 0.4480 inches

#### Flange Width:

Between 0.0200 inches and 0.0400 inches

#### Corner Shape:

Square outside right corner

#### Hardness Rating:

32.0 rockwell c and 36.0 rockwell c

#### Surface Finish:

125.0 microinches intermediate layer

## Material:

Steel comp 4140

## **Material Specification:**

Mil-s-5626 military specification single material response

# Surface Treatment:

Cadmium

## Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

## Style Designator:

22c solid, external flange one end

## **Test Data Document:**

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Shelf Life:

N/a

# Unit Of Measure:

```
--
```

#### Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-s-5626 spec.