## NSN 3120-00-922-8301

Sleeve Bushing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3120-00-922-8301

		_					
Hol	_	ı	12	m	0	ŀ۵	r-

0.1390 inches first and 0.1440 inches first

**Overall Length:** 

Between 0.3650 inches and 0.3850 inches

**Body Outside Diameter:** 

Between 0.4700 inches and 0.4800 inches

**Body Inside Diameter:** 

Between 0.3745 inches and 0.3750 inches

Flange Outside Diameter:

Between 1.2400 inches and 1.2600 inches

Flange Width:

Between 0.0500 inches and 0.0700 inches

**Interior Flange Hole Diameter:** 

Between 0.3120 inches and 0.3130 inches

**Interior Flange Left End To Centerline Distance:** 

Between 0.1825 inches and 0.1925 inches

Interior Flange Width:

Between 0.0650 inches and 0.1050 inches

**Corner Shape:** 

Square outside right corner

Surface Finish:

32.0 microinches inside diameter surface of body

**Antirotation/lubrication Type And Quantity:** 

2 hole

**Special Features:** 

2 holes located on 180 degrees line of flange 0.500 in. From centerline tocenter of hole, positioning slot in periphery of flange 0.140 in. W located 90 degrees from mtg holes

Material:

Aluminum alloy 2014

**Surface Treatment:** 

Anodize

**Surface Treatment Specification:** 

Mil-a-8625, type 1 military specification single treatment response

Style Designator:

22c-2 solid, external flange one end, interior flang (s) not located at either end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A045a0

## NSN 3120-00-922-8301

Sleeve Bushing - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.