NSN 3120-00-927-5814 Sleeve Bushing - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/3120-00-927-5814 |
|---|
| Overall Length: |
| Between 0.3300 inches and 0.3350 inches |
| Body Outside Diameter: |
| Between 0.3756 inches and 0.3761 inches |
| Body Inside Diameter: |
| Between 0.3160 inches and 0.3190 inches |
| Flange Outside Diameter: |
| Between 0.4200 inches and 0.4400 inches |
| Flange Width: |
| Between 0.0300 inches and 0.0350 inches |
| Corner Shape: |
| Square outside right corner |
| Hardness Rating: |
| 28.0 rockwell c and 35.0 rockwell c |
| Surface Finish: |
| 125.0 microinches intermediate layer |
| Material: |
| Steel comp 4130 |
| Material Specification: |
| Mil-s-6758 cond d military specification single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Ps 13101, type 2, cl 3, mcdonnell douglas corporation mfr ref single treatment response |
| Style Designator: |
| 22c solid, external flange one end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A045a0 |
| Mil-std (military Standard): |

Mil-s-6758 spec.