## NSN 3120-00-932-3682

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-932-3682

| View Online at https://aerobasegroup.com/nsn/3120-00-932-3682   |
|---|
| Overall Length:   |
| Between 0.4110 inches and 0.4150 inches   |
| Body Outside Diameter:  |
| Between 0.4900 inches and 0.5100 inches   |
| Body Inside Diameter:   |
| Between 0.3950 inches and 0.3980 inches   |
| Flange Outside Diameter:  |
| Between 0.6900 inches and 0.7100 inches   |
| Flange Width:   |
| Between 0.0800 inches and 0.1000 inches   |
| Corner Shape:   |
| Square outside right corner   |
| Hardness Rating:  |
| 26.0 rockwell c and 33.0 rockwell c   |
| Surface Finish:   |
| 125.0 microinches intermediate layer  |
| Material:   |
| Steel comp 4130   |
| Material Specification:   |
| Mil-s-6758 military specification single material response  |
| Surface Treatment:  |
| Cadmium   |
| Surface Treatment Specification:  |
| Qq-p-416 federal specification single treatment response  |
| Style Designator:   |
| 22c solid, external flange one end  |
| Test Data Document:   |
| 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain         |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                           |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A045a0  |

Mil-std (military Standard):

Mil-s-6758 spec.