# NSN 3120-00-939-3554

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-939-3554

$\sim$					
×1	∩t.	W	ın	tn	٠.
v	vι	**	ıu	ш	

0.1000 inches first and 0.1200 inches first

### Slot Length:

0.4000 inches first and 0.4200 inches first

# **Overall Length:**

Between 0.9350 inches and 0.9450 inches

### **Body Outside Diameter:**

Between 2.1644 inches and 2.1648 inches

### **Body Inside Diameter:**

Between 1.8400 inches and 1.8600 inches

### **Interior Flange Hole Diameter:**

Between 1.6400 inches and 1.6600 inches

### **Interior Flange Left End To Centerline Distance:**

Between 0.1700 inches and 0.1800 inches

### **Interior Flange Width:**

Between 0.0600 inches and 0.0800 inches

# **Lubricant Accommodation Style:**

Grooved circular

# Corner Shape:

Square inside right corner

# **Hardness Rating:**

30.0 rockwell c and 38.0 rockwell c

# **Antirotation/lubrication Type And Quantity:**

8 slot

# **Surface Groove Location And Quantity:**

1 internal

# Material:

Steel comp 410

### **Material Specification:**

Ams 5613 assn standard single material response

# Style Designator:

17c-2 solid, plain, no outside flanges, interior flang (s) not located at either end

# Shelf Life:

N/a

### **Unit Of Measure:**

--

#### **Demilitarization:**

Yes - demil/mli

# Fiig:

A045a0