NSN 3120-00-939-3554

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-939-3554

| \sim | | | | | |
|--------|-----|----|----|----|----|
| ×1 | ∩t. | W | ın | tn | ٠. |
| v | vι | ** | ıu | ш | |

0.1000 inches first and 0.1200 inches first

Slot Length:

0.4000 inches first and 0.4200 inches first

Overall Length:

Between 0.9350 inches and 0.9450 inches

Body Outside Diameter:

Between 2.1644 inches and 2.1648 inches

Body Inside Diameter:

Between 1.8400 inches and 1.8600 inches

Interior Flange Hole Diameter:

Between 1.6400 inches and 1.6600 inches

Interior Flange Left End To Centerline Distance:

Between 0.1700 inches and 0.1800 inches

Interior Flange Width:

Between 0.0600 inches and 0.0800 inches

Lubricant Accommodation Style:

Grooved circular

Corner Shape:

Square inside right corner

Hardness Rating:

30.0 rockwell c and 38.0 rockwell c

Antirotation/lubrication Type And Quantity:

8 slot

Surface Groove Location And Quantity:

1 internal

Material:

Steel comp 410

Material Specification:

Ams 5613 assn standard single material response

Style Designator:

17c-2 solid, plain, no outside flanges, interior flang (s) not located at either end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A045a0