

View Online at <https://aerobasegroup.com/nsn/3120-00-948-7176>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Style:**

Externally threaded

**Overall Length:**

2.5930 inches

**Bore Diameter:**

Between 0.6245 inches and 0.6250 inches

**Outer Member Outside Diameter:**

1.6860 inches

**Bore Center To Shank End Distance:**

2.7500 inches

**Outer Member Width:**

Between 0.4950 inches and 0.5050 inches

**Inner Member Width:**

Between 0.6230 inches and 0.6250 inches

**Shank Thread Length:**

1.7820 inches

**Static Radial Load Rating:**

32200 pounds

**Thread Diameter:**

0.750 inches

**Thready Qty Per Inch (tpi):**

16

**Hardness Rating:**

24.0 rockwell c outer race member and 35.0 rockwell c outer race member

**Special Features:**

Entire thd lg slotted longitudinally 0.1250 in. Min, 0.1300 in. Max w by 0.0870 in. Min, 0.0920 in. Maximum deep

**Material:**

Steel rod end body

**Surface Treatment:**

Cadmium race liner

**Style Designator:**

Ball type

**Test Data Document:**

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A045a0