

View Online at <https://aerobasegroup.com/nsn/3120-00-950-9493>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Style:**

Externally threaded

**Overall Length:**

4.3120 inches

**Bore Diameter:**

Between 0.6245 inches and 0.6250 inches

**Outer Member Outside Diameter:**

1.6240 inches

**Bore Center To Shank End Distance:**

3.5000 inches

**Outer Member Width:**

Between 0.4950 inches and 0.5050 inches

**Inner Member Width:**

Between 0.9950 inches and 1.0000 inches

**Shank Thread Length:**

2.5000 inches

**Static Radial Load Rating:**

174000 pounds

**Thread Diameter:**

1.125 inches

**Features Provided:**

Flush lubrication fitting

**Thready Qty Per Inch (tpi):**

12

**Hardness Rating:**

39.0 rockwell c rod end body and 42.0 rockwell c rod end body

**Lubrication Feature:**

Perforation external surface member

**Special Features:**

Thd end of shank drilled longitudinally 0.1870 in. Min 0.1920 in. Maximum w by 0.1150 in. Min 0.1200 in. Maximum deep

**Material:**

Steel rod end body

**Surface Treatment:**

Cadmium rod end body

**Style Designator:**

Ball type

**Test Data Document:**

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0