

View Online at <https://aerobasegroup.com/nsn/3120-00-950-9941>

Overall Length:

Between 0.8900 inches and 0.9300 inches

Body Outside Diameter:

Between 0.4980 inches and 0.4985 inches

Body Inside Diameter:

Between 0.2650 inches and 0.2720 inches

Flange Outside Diameter:

Between 0.7400 inches and 0.7600 inches

Flange Width:

Between 0.1150 inches and 0.1350 inches

Corner Shape:

Square outside left corner

Surface Finish:

63.0 microinches outside diameter surface of body

Special Features:

Flange end out of round, distance across wrenching flats 0.6100 in. Min, 0.6300 in. Max, internally thd 0.3750 in. Dia, 24 thd per in., unf series class 3 fit, 0.2500 in. Lg, outside corner of thd hole chamfered 0.0200 in. Min, 0.0400 in. Max, 45.0 angle, inside corner chamfered 0.0465 in. Min, 0.0600 in. Max, 30.0 angle

Material:

Steel comp 4130

Material Specification:

Mil-s-6758, d4 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Style Designator:

22c solid, external flange one end

Test Data Document:

97499-bps4075 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-s-6758 spec.