

View Online at <https://aerobasegroup.com/nsn/3120-00-954-9913>

Thread Class:

3a

Thread Direction:

Left-hand

Shank Style:

Externally threaded

Overall Length:

Between 2.6870 inches and 2.6980 inches

Bore Diameter:

Between 0.4370 inches and 0.4390 inches

Outer Member Outside Diameter:

Between 1.1150 inches and 1.1350 inches

Bore Center To Shank End Distance:

Between 2.1150 inches and 2.1350 inches

Outer Member Width:

Between 0.4320 inches and 0.4420 inches

Inner Member Width:

Between 0.5570 inches and 0.5620 inches

Shank Thread Length:

1.3750 inches

Static Radial Load Rating:

4633 pounds

Thread Diameter:

0.438 inches

Features Provided:

External lubrication fitting

Thready Qty Per Inch (tpi):

20

Hardness Rating:

60.0 rockwell c inner member

Lubrication Feature:

Groove internal outer member

Material:

Steel comp e50100 inner member or steel comp e51100 inner member

Surface Treatment:

Cadmium rod end body

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response rod end body

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0