

View Online at <https://aerobasegroup.com/nsn/3120-00-954-9913>

**Thread Class:**

3a

**Thread Direction:**

Left-hand

**Shank Style:**

Externally threaded

**Overall Length:**

Between 2.6870 inches and 2.6980 inches

**Bore Diameter:**

Between 0.4370 inches and 0.4390 inches

**Outer Member Outside Diameter:**

Between 1.1150 inches and 1.1350 inches

**Bore Center To Shank End Distance:**

Between 2.1150 inches and 2.1350 inches

**Outer Member Width:**

Between 0.4320 inches and 0.4420 inches

**Inner Member Width:**

Between 0.5570 inches and 0.5620 inches

**Shank Thread Length:**

1.3750 inches

**Static Radial Load Rating:**

4633 pounds

**Thread Diameter:**

0.438 inches

**Features Provided:**

External lubrication fitting

**Thready Qty Per Inch (tpi):**

20

**Hardness Rating:**

60.0 rockwell c inner member

**Lubrication Feature:**

Groove internal outer member

**Material:**

Steel comp e50100 inner member or steel comp e51100 inner member

**Surface Treatment:**

Cadmium rod end body

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 2 federal specification single treatment response rod end body

**Style Designator:**

Ball type

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0