NSN 3120-00-957-1103

Sleeve Bushing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3120-00-957-1103

		_					
Hol	ΙΔ.	11	ıor	m	5 †	ar	

0.0920 inches first and 0.0970 inches first

Overall Length:

Between 0.5220 inches and 0.5320 inches

Body Outside Diameter:

Between 0.6258 inches and 0.6267 inches

Body Inside Diameter:

Between 0.4930 inches and 0.4950 inches

Flange Outside Diameter:

Between 0.8650 inches and 0.8750 inches

Flange Width:

Between 0.0570 inches and 0.0620 inches

Lubricant Accommodation Style:

Grooved circular

Corner Shape:

Square outside right corner

Hardness Rating:

33.0 rockwell c and 37.0 rockwell c

Surface Finish:

125.0 microinches intermediate layer

Antirotation/lubrication Type And Quantity:

6 hole

Surface Groove Location And Quantity:

1 external

Material:

Steel comp 4130

Material Specification:

Mil-s-6758, c4 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Style Designator:

Solid, external flange one end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0

NSN 3120-00-957-1103

Sleeve Bushing - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.