# NSN 3120-00-957-1103

Sleeve Bushing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3120-00-957-1103

		_				
Hol	ΙΔ.	11	ıor	ne	<b>3</b> + 4	ar.

0.0920 inches first and 0.0970 inches first

#### **Overall Length:**

Between 0.5220 inches and 0.5320 inches

#### **Body Outside Diameter:**

Between 0.6258 inches and 0.6267 inches

#### **Body Inside Diameter:**

Between 0.4930 inches and 0.4950 inches

#### Flange Outside Diameter:

Between 0.8650 inches and 0.8750 inches

#### Flange Width:

Between 0.0570 inches and 0.0620 inches

#### **Lubricant Accommodation Style:**

Grooved circular

#### **Corner Shape:**

Square outside right corner

#### **Hardness Rating:**

33.0 rockwell c and 37.0 rockwell c

#### **Surface Finish:**

125.0 microinches intermediate layer

# **Antirotation/lubrication Type And Quantity:**

6 hole

## **Surface Groove Location And Quantity:**

1 external

#### Material:

Steel comp 4130

# **Material Specification:**

Mil-s-6758, c4 military specification single material response

#### **Surface Treatment:**

Cadmium

# **Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

#### **Style Designator:**

Solid, external flange one end

#### Shelf Life:

N/a

#### **Unit Of Measure:**

--

### Demilitarization:

No

#### Fiig:

A045a0

# NSN 3120-00-957-1103

Sleeve Bushing - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.