

View Online at <https://aerobasegroup.com/nsn/3120-00-966-8051>

**Slot Width:**

0.3000 inches first and 0.3200 inches first

**Slot Length:**

0.9800 inches first and 1.0200 inches first

**Overall Length:**

Between 2.3700 inches and 2.4100 inches

**Body Outside Diameter:**

Between 2.6330 inches and 2.6340 inches

**Body Inside Diameter:**

Between 2.4240 inches and 2.4280 inches

**Flange Outside Diameter:**

Between 2.8400 inches and 2.8600 inches

**Flange Width:**

Between 0.1000 inches and 0.1200 inches

**Right Internal Flange Hole Diameter:**

Between 2.2100 inches and 2.2300 inches

**Right Internal Flange Width:**

Between 0.0660 inches and 0.0900 inches

**Left Flange Outside Diameter:**

Between 2.8400 inches and 2.8600 inches

**Left Flange Width:**

Between 0.2500 inches and 0.2900 inches

**Lubricant Accommodation Style:**

Grooved circular

**End To Flange Distance:**

Between 0.9000 inches and 0.9200 inches

**Hardness Rating:**

32.0 rockwell c and 38.0 rockwell c

**Antirotation/lubrication Type And Quantity:**

3 slot

**Surface Groove Location And Quantity:**

1 internal

**Material:**

Steel comp 8740

**Material Specification:**

Ams 6322 assn standard single material response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A045a0