## NSN 3120-00-966-8051

Sleeve Bushing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3120-00-966-8051

**Slot Width:** 

0.3000 inches first and 0.3200 inches first

Slot Length:

0.9800 inches first and 1.0200 inches first

**Overall Length:** 

Between 2.3700 inches and 2.4100 inches

**Body Outside Diameter:** 

Between 2.6330 inches and 2.6340 inches

**Body Inside Diameter:** 

Between 2.4240 inches and 2.4280 inches

Flange Outside Diameter:

Between 2.8400 inches and 2.8600 inches

Flange Width:

Between 0.1000 inches and 0.1200 inches

**Right Internal Flange Hole Diameter:** 

Between 2.2100 inches and 2.2300 inches

**Right Internal Flange Width:** 

Between 0.0660 inches and 0.0900 inches

Left Flange Outside Diameter:

Between 2.8400 inches and 2.8600 inches

Left Flange Width:

Between 0.2500 inches and 0.2900 inches

**Lubricant Accommodation Style:** 

Grooved circular

**End To Flange Distance:** 

Between 0.9000 inches and 0.9200 inches

**Hardness Rating:** 

32.0 rockwell c and 38.0 rockwell c

**Antirotation/lubrication Type And Quantity:** 

3 slot

**Surface Groove Location And Quantity:** 

1 internal

Material:

Steel comp 8740

**Material Specification:** 

Ams 6322 assn standard single material response

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

## **NSN 3120-00-966-8051** Sleeve Bushing - Page 2 of 2



Fiig:

A045a0