

View Online at <https://aerobasegroup.com/nsn/3120-00-970-3620>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

3.7185 inches

Bore Diameter:

Between 0.6250 inches and 0.6255 inches

Lubrication Material:

Lubricant, dry film

Outer Member Outside Diameter:

1.4370 inches

Bore Center To Shank End Distance:

3.0000 inches

Outer Member Width:

0.5000 inches

Inner Member Width:

Between 0.6230 inches and 0.6250 inches

Shank Thread Length:

2.0000 inches

Static Radial Load Rating:

8800 pounds

Thread Diameter:

0.625 inches

Features Provided:

Flush lubrication fitting

Thready Qty Per Inch (tpi):

18

Special Features:

Keyway in shank

Surface Treatment:

Cadmium rod end body

Style Designator:

Ball type

Test Data Document:

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A045a0