

View Online at <https://aerobasegroup.com/nsn/3120-00-980-0344>

Thread Class:

3b

Thread Direction:

Right-hand

Shank Style:

Internally threaded w/bead and wrench flats and inspection hole

Overall Length:

Between 1.8735 inches and 1.9160 inches

Bore Diameter:

Between 0.2494 inches and 0.2497 inches

Outer Member Outside Diameter:

1.0000 inches

Bore Center To Shank End Distance:

Between 1.3960 inches and 1.4160 inches

Outer Member Width:

0.4060 inches

Inner Member Width:

Between 0.6500 inches and 0.6600 inches

Shank End To Shoulder Length:

Between 0.8960 inches and 0.9160 inches

Shank Thread Length:

Between 0.7200 inches and 0.8100 inches

Inspection Hole Center To End Distance:

Between 0.4010 inches and 0.4110 inches

Shank Width Across Wrench Flats:

Between 0.4270 inches and 0.4370 inches

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

61.0 rockwell c race insert

Material:

Steel rod end body

Material Specification:

Fed-std-66 federal standard single material response race liner

Surface Treatment:

Cadmium rod end body

Style Designator:

Ball type extended one side

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0