

View Online at <https://aerobasegroup.com/nsn/3120-00-983-0120>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

Between 5.6475 inches and 5.7300 inches

Bore Diameter:

Between 0.6245 inches and 0.6250 inches

Outer Member Outside Diameter:

Between 2.6150 inches and 2.6600 inches

Bore Center To Shank End Distance:

Between 4.3400 inches and 4.4000 inches

Outer Member Width:

Between 1.0000 inches and 1.0100 inches

Inner Member Width:

Between 1.4980 inches and 1.5000 inches

Shank Thread Length:

Between 2.3400 inches and 2.4000 inches

Thread Diameter:

0.750 inches

Thread Qty Per Inch (tpi):

16

Hardness Rating:

56.0 rockwell c inner member

Special Features:

Hole drilled through shank axis 0.3020 in. Min, 0.3220 in. Maximum diameter 2.2800 in. Min, 2.3404 in. Maximum deep

Material:

Steel rod end body

Material Specification:

209-010-443, 97499 mfr ref single material response rod end body

Test Data Document:

97499-bps-fw-4089 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A045a0