

View Online at <https://aerobasegroup.com/nsn/3120-00-983-0120>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Style:**

Externally threaded

**Overall Length:**

Between 5.6475 inches and 5.7300 inches

**Bore Diameter:**

Between 0.6245 inches and 0.6250 inches

**Outer Member Outside Diameter:**

Between 2.6150 inches and 2.6600 inches

**Bore Center To Shank End Distance:**

Between 4.3400 inches and 4.4000 inches

**Outer Member Width:**

Between 1.0000 inches and 1.0100 inches

**Inner Member Width:**

Between 1.4980 inches and 1.5000 inches

**Shank Thread Length:**

Between 2.3400 inches and 2.4000 inches

**Thread Diameter:**

0.750 inches

**Thready Qty Per Inch (tpi):**

16

**Hardness Rating:**

56.0 rockwell c inner member

**Special Features:**

Hole drilled through shank axis 0.3020 in. Min, 0.3220 in. Maximum diameter 2.2800 in. Min, 2.3404 in. Maximum deep

**Material:**

Steel rod end body

**Material Specification:**

209-010-443, 97499 mfr ref single material response rod end body

**Test Data Document:**

97499-bps-fw-4089 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0