

View Online at <https://aerobasegroup.com/nsn/3120-00-985-3761>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Style:**

Externally threaded

**Overall Length:**

1.2810 inches

**Bore Diameter:**

Between 0.1895 inches and 0.1925 inches

**Outer Member Outside Diameter:**

Between 0.5520 inches and 0.5620 inches

**Bore Center To Shank End Distance:**

Between 0.9680 inches and 1.0310 inches

**Outer Member Width:**

Between 0.1770 inches and 0.1970 inches

**Inner Member Width:**

Between 0.2450 inches and 0.2500 inches

**Shank Thread Length:**

0.5930 inches

**Static Radial Load Rating:**

2100 pounds

**Thread Diameter:**

0.250 inches

**Features Provided:**

Flush lubrication fitting

**Thready Qty Per Inch (tpi):**

28

**Lubrication Feature:**

Groove internal inner member

**Special Features:**

Max radial clearance 0.0005 t/i/r/. Nas 559 keyway in shank

**Material:**

Steel comp e52100 inner member

**Surface Treatment:**

Cadmium rod end body

**Style Designator:**

Ball type

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A045a0