NSN 3120-00-986-6048

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-986-6048

View Online at https://aerobasegroup.com/nsn/3120-00-986-6048
Overall Length:
Between 1.3100 inches and 1.3300 inches
Body Outside Diameter:
Between 1.0015 inches and 1.0020 inches
Body Inside Diameter:
Between 0.8490 inches and 0.8690 inches
Flange Outside Diameter:
Between 1.2400 inches and 1.2600 inches
Flange Width:
Between 0.0430 inches and 0.0440 inches
Corner Shape:
Square outside right corner
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Surface Finish:
90.0 microinches intermediate layer
Special Features:
Closed end of id flat bottom drilled, tin-plated 0.0002 to 0.0003 in. Thk o/a
Material:
Steel
Material Specification:
Mil-s-5000 comp 4340 military specification single material response
Surface Treatment:
Tin alloy
Surface Treatment Specification:
Mil-t-10727 military specification single treatment response
Style Designator:
22c solid, external flange one end
Test Data Document:
81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:

Mil-std (military Standard): Mil-s-5000 spec.

A045a0