

View Online at <https://aerobasegroup.com/nsn/3120-00-995-6895>

Thread Class:

2b

Thread Direction:

Right-hand

Shank Style:

Internally threaded w/bead and wrench flats and inspection hole

Overall Length:

2.1250 inches

Bore Diameter:

Between 0.3745 inches and 0.3765 inches

Outer Member Outside Diameter:

Between 0.9900 inches and 1.0100 inches

Bore Center To Shank End Distance:

Between 1.6150 inches and 1.6350 inches

Outer Member Width:

Between 0.4012 inches and 0.4112 inches

Inner Member Width:

Between 0.4950 inches and 0.5000 inches

Shank Thread Length:

0.9370 inches

Inspection Hole Center To End Distance:

0.4690 inches

Shank Width Across Wrench Flats:

0.5620 inches

Static Radial Load Rating:

4451 pounds

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

60.0 rockwell c inner member

Lubrication Feature:

Groove race insert

Special Features:

Magnetic particle inspection required

Material:

Steel rod end body

Material Specification:

Qq-b-637; comp 2 federal specification single material response race insert

Surface Treatment:

Cadmium rod end body

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0