

View Online at <https://aerobasegroup.com/nsn/3120-01-004-4937>

Bore Diameter:

Between 0.4995 inches and 0.5000 inches

Outer Member Outside Diameter:

Between 0.9995 inches and 1.0000 inches

Outer Member Width:

Between 0.5000 inches and 0.5100 inches

Inner Member Width:

Between 0.6230 inches and 0.6250 inches

Static Radial Load Rating:

28000 pounds

Hardness Rating:

55.0 rockwell c inner member and 60.0 rockwell c inner member

Lubrication Feature:

Self-lubricating liner inside diameter surface of body

Special Features:

Misalignment perm 10 deg; notch in outer race member 0.049 in. Min to 0.055 in. Maximum I, 0.035 in. Min to 0.040 in. Maximum deep, 0.010 in. Min to 0.020 in. Maximum r

Material:

Steel comp 630 race insert

Material Specification:

Kahr-lon, cagec 97613 mfr ref single material response race liner

Surface Treatment:

Cadmium race insert and chromate race insert

Surface Treatment Specification:

Qq-p-416, class 2, type 2 federal specification single treatment response race insert

Style Designator:

With insert and/or liner

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0