

View Online at <https://aerobasegroup.com/nsn/3120-01-008-5435>

Thread Class:

3b

Thread Direction:

Left-hand

Shank Style:

Internally threaded w/bead and wrench flats and inspection hole

Overall Length:

2.7810 inches

Bore Diameter:

Between 0.4995 inches and 0.5015 inches

Outer Member Outside Diameter:

Between 1.3020 inches and 1.3220 inches

Bore Center To Shank End Distance:

Between 2.1150 inches and 2.1350 inches

Outer Member Width:

Between 0.4950 inches and 0.5050 inches

Inner Member Width:

Between 0.6200 inches and 0.6250 inches

Shank Thread Length:

1.1870 inches

Inspection Hole Center To End Distance:

Between 0.5890 inches and 0.5990 inches

Shank Width Across Wrench Flats:

Between 0.7400 inches and 0.7600 inches

Static Radial Load Rating:

7436 pounds

Thread Diameter:

0.500 inches

Features Provided:

External lubrication fitting

Thready Qty Per Inch (tpi):

20

Hardness Rating:

60.0 rockwell c inner member

Lubrication Feature:

Groove race insert

Material:

Steel rod end body

Surface Treatment:

Cadmium rod end body and chromate rod end body

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response rod end body

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0