# NSN 3120-01-009-6774

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-009-6774

### **Overall Length:**

Between 0.4850 inches and 0.4900 inches

#### Body Outside Diameter:

Between 0.8760 inches and 0.8770 inches

#### Body Inside Diameter:

Between 0.7495 inches and 0.7505 inches

#### Corner Shape:

Square all corners

#### Surface Finish:

125.0 microinches intermediate layer

#### Material:

Steel comp 4130 or steel comp 4135

## Material Specification:

Mil-t-6736, cond n military specification single material response or ams 6372 assn standard single material response

#### Surface Treatment:

Cadmium right end surface of body and chromate right end surface of body

## Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification all treatment responses outside diameter surface of body

## Style Designator:

17c solid, plain, no outside flanges

## Test Data Document:

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Specification Data:

43999-Id137-0028 manufacturers specification and 43999-Id137-0029 manufacturers specification and 43999-Id137-0030 manufacturers specification

## Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

```
Fiig:
```

A045a0

Mil-std (military Standard):

Mil-t-6736 spec.