NSN 3120-01-011-9721

Sleeve Bushing - Page 1 of 1



Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:	View Online at https://aerobasegroup.com/nsn/3120-01-011-9721
Overall Length: Between 0.4950 inches and 0.5000 inches Body Outside Diameter: Between 1.471 inches and 1.4726 inches Body Inside Diameter: Between 1.2350 inches and 1.2450 inches Flange Outside Diameter: Between 1.2350 inches and 1.2450 inches Flange Width: Between 0.1150 inches Flange Width: Between 0.1150 inches and 0.1200 inches Lubricant Accommodation Style: Grooved circular Corner Shape: Undercut left flange body corner Hardness Rating: 30, Tockwell c and 43.0 rockwell c Antirotation/Jubrication Type And Quantity: 1 hole Surface Groove Location And Quantity: 1 hole Surface Treatment: Tin Style Designator: 22c solid, external flange one end Test Data Document: 81349-mill-1868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mill-18950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mill-18950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	Hole Diameter:
Between 0.4950 inches and 0.5000 inches Body Outside Diameter: Between 1.4711 inches and 1.4726 inches Body Inside Diameter: Between 1.2350 inches and 1.2450 inches Flange Outside Diameter: 1.7500 inches Flange Width: Between 0.1150 inches and 0.1200 inches Lubricant Accommodation Style: Grooved diroular Corner Shape: Undercut left flange body corner Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Antirotation/flubrication Type And Quantity: 1 hole Surface Groove Location And Quantity: 1 external and 1 internal Material: Steel comp 4130 Surface Treatment: Tin Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-1-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-1-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-1-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheff Life: N/a Unit Of Measure:	0.1250 inches first
Body Outside Diameter: Between 1.4711 inches and 1.4726 inches Body Inside Diameter: Between 1.2350 inches and 1.2450 inches Flange Outside Diameter: 1.7500 inches Flange Width: Between 0.1150 inches and 0.1200 inches Lubricant Accommodation Style: Grooved circular Corner Shape: Undercut left flange body corner Hardness Rating: 30.0 rockwell c and 43.0 rockwell c Antirotation/Jubrication Type And Quantity: 1 hole Surface Groove Location And Quantity: 1 hole Surface Groove Location And Quantity: 2 test comp 4130 Surface Treatment: Tin Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-1-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions, brachures, etc., that reflect specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: ""." ""	Overall Length:
Between 1.4711 inches and 1.4726 inches Body Inside Diameter: Between 1.2350 inches and 1.2450 inches Flange Width: Botween 0.1350 inches and 0.1200 inches Flange Width: Botween 0.1150 inches and 0.1200 inches Lubricant Accommodation Style: Growed circular Corner Shape: Undercut left flange body corner Hardness Rating: 30.0 rockwell c and 43.0 rockwell c Antirotation/Jubrication Type And Quantity: 1 hole Surface Groove Location And Quantity: 1 external and 1 internal Material: Steel comp 4130 Surface Treatment: Tin Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-16868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). And \$4349-mil-1895 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). And \$4349-mil-1895 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Unit Of Measure:	Between 0.4950 inches and 0.5000 inches
Body Inside Diameter: Between 1.2350 inches and 1.2450 inches Flange Width: Between 0.150 inches Flange Width: Between 0.150 inches and 0.1200 inches Lubricant Accommodation Style: Grooved circular Corner Shape: Undercut left flange body corner Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Antirotation/fubrication Type And Quantity: 1 hole Surface Groove Location And Quantity: 1 totalernal and 1 internal Material: Steel comp 4130 Surface Treatment: Tin Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Na Unit Of Measure:	Body Outside Diameter:
Between 1.2350 inches and 1.2450 inches Flange Outside Diameter: 1.7500 inches Flange Width: Between 0.1150 inches and 0.1200 inches Lubricant Accommodation Style: Grooved circular Corner Shape: Undercut left flange body corner Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Antirotation/flubrication Type And Quantity: 1 hole Surface Groove Location And Quantity: 1 texternal and 1 internal Material: Steel comp 4130 Surface Treatment: Tin Style Designator: 22c solid, external flange one end Test Data Document: 81349-mili-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). And 81349-mili-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). And 81349-mili-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Na Unit Of Measure:	Between 1.4711 inches and 1.4726 inches
Flange Outside Diameter: 1.7500 inches Flange Width: Between 0.1150 inches and 0.1200 inches Lubricant Accommodation Style: Grooved circular Corner Shape: Undercut left flange body comer Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Antirotation/flubrication Type And Quantity: 1 hole Surface Groove Location And Quantity: 1 external and 1 internal Material: Steel comp 4130 Surface Treatment: Tin Style Designator: 22c solid, external flange one end Test Data Document: 31349-mil-i-8686 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-8950 Shelf Life: Na Unit Of Measure:	Body Inside Diameter:
1.7500 inches Flange Width: Between 0.1150 inches and 0.1200 inches Lubricant Accommodation Style: Grooved circular Corner Shape: Undercut left flange body corner Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Antirotation/lubrication Type And Quantity: 1 hole Surface Groove Location And Quantity: 1 external and 1 internal Material: Steel comp 4130 Surface Treatment: Tin Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil+6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil+8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil+8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Between 1.2350 inches and 1.2450 inches
Flange Width: Between 0.1150 inches and 0.1200 inches Lubricant Accommodation Style: Grooved circular Corner Shape: Undercut left flange body comer Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Antirotation/flubrication Type And Quantity: 1 hole Surface Groove Location And Quantity: 1 hole Surface Treatment Steel comp 4130 Surface Treatment: Tin Style Designator: 22c solid, external flange one end Test Data Document: 81349-mili-1868s specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mili-18950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mili-18950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Flange Outside Diameter:
Between 0.1150 inches and 0.1200 inches Lubricant Accommodation Style: Grooved circular Corner Shape: Undercut left flange body corner Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Antirotation/lubrication Type And Quantity: 1 hole Surface Groove Location And Quantity: 1 external and 1 internal Material: Steel comp 4130 Surface Treatment: Tin Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	1.7500 inches
Lubricant Accommodation Style: Grooved circular Corner Shape: Undercut left flange body corner Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Antirotation/lubrication Type And Quantity: 1 hole Surface Groove Location And Quantity: 1 external and 1 internal Material: Steel comp 4130 Surface Treatment: Tin Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-8850 specification (includes engineering type bulletins, brochures, etc., that reflect specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-8850 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Flange Width:
Grooved circular Corner Shape: Undercut left flange body corner Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Antirotation/lubrication Type And Quantity: 1 hole Surface Groove Location And Quantity: 1 external and 1 internal Material: Steel comp 4130 Surface Treatment: Tin Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-+6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "*, etc.). And 81349-mil-i-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification environmental and performance requirements and test conditions that are shown as "typical", "average", "*, etc.). And 81349-mil-i-8950 commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "*, etc.). Shelf Life: N/a Unit Of Measure:	Between 0.1150 inches and 0.1200 inches
Corner Shape: Undercut left flange body corner Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Antirotation/flubrication Type And Quantity: 1 hole Surface Groove Location And Quantity: 1 external and 1 internal Material: Steel comp 4130 Surface Treatment: Tin Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Lubricant Accommodation Style:
Undercut left flange body corner Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Antirotation/lubrication Type And Quantity: 1 hole Surface Groove Location And Quantity: 1 external and 1 internal Material: Steel comp 4130 Surface Treatment: Tin Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Grooved circular
Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Antirotation/lubrication Type And Quantity: 1 hole Surface Groove Location And Quantity: 1 external and 1 internal Material: Steel comp 4130 Surface Treatment: Tin Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Corner Shape:
39.0 rockwell c and 43.0 rockwell c Antirotation/lubrication Type And Quantity: 1 hole Surface Groove Location And Quantity: 1 external and 1 internal Material: Steel comp 4130 Surface Treatment: Tin Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Undercut left flange body corner
Antirotation/lubrication Type And Quantity: 1 hole Surface Groove Location And Quantity: 1 external and 1 internal Material: Steel comp 4130 Surface Treatment: Tin Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Hardness Rating:
1 hole Surface Groove Location And Quantity: 1 external and 1 internal Material: Steel comp 4130 Surface Treatment: Tin Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	39.0 rockwell c and 43.0 rockwell c
Surface Groove Location And Quantity: 1 external and 1 internal Material: Steel comp 4130 Surface Treatment: Tin Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Antirotation/lubrication Type And Quantity:
Material: Steel comp 4130 Surface Treatment: Tin Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	1 hole
Material: Steel comp 4130 Surface Treatment: Tin Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Surface Groove Location And Quantity:
Steel comp 4130 Surface Treatment: Tin Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	1 external and 1 internal
Surface Treatment: Tin Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Material:
Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Steel comp 4130
Style Designator: 22c solid, external flange one end Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Surface Treatment:
Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Tin
Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Style Designator:
81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	22c solid, external flange one end
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-8950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-8950
performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes
Shelf Life: N/a Unit Of Measure:	commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and
N/a Unit Of Measure:	performance requirements and test conditions that are shown as "typical", "average", "", etc.).
N/a Unit Of Measure:	Shelf Life:
	N/a
	Unit Of Measure:
Demilitarization:	
	Demilitarization:
No	
	Fiig:
FIIO:	' "g·

A045a0