NSN 3120-01-015-3066

Sleeve Bushing - Page 1 of 1



| ٧ | /iew Online at https://aerobasegroup.com/nsn/3120-01-015-3066 |
|---|--|
| C | Overall Length: |
| Е | Between 0.2320 inches and 0.2470 inches |
| E | Body Outside Diameter: |
| Е | Between 0.3756 inches and 0.3761 inches |
| Е | Body Inside Diameter: |
| В | Between 0.2380 inches and 0.2430 inches |
| F | Flange Outside Diameter: |
| Е | Between 0.4900 inches and 0.5100 inches |
| F | Flange Width: |
| Е | Between 0.0570 inches and 0.0620 inches |
| C | Corner Shape: |
| ι | Indercut left flange body corner |
| Ν | Material: |
| S | Steel comp 630 or steel comp xm-12 |
| Ν | Material Specification: |
| Α | Ams 5643 assn standard 1st material response or ams 5659 assn standard 2nd material response |
| S | Surface Treatment: |
| F | Passivate |
| S | Surface Treatment Specification: |
| C | Qq-p-35 federal specification single treatment response |
| S | Style Designator: |
| 2 | 22c solid, external flange one end |
| S | Shelf Life: |
| ١ | N/a |
| ι | Init Of Measure: |
| - | - |
| C | Demilitarization: |
| ١ | No |
| F | iig: |
| Α | N045a0 |