## NSN 3120-01-015-5786

Sleeve Bushing - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/3120-01-015-5786                  |                 |
|--|-----------------|
| Overall Length:  |                 |
| Between 0.3320 inches and 0.3470 inches  |                 |
| Body Outside Diameter:   |                 |
| Between 0.5006 inches and 0.5013 inches  |                 |
| Body Inside Diameter:  |                 |
| Between 0.3590 inches and 0.3660 inches  |                 |
| Flange Outside Diameter:   |                 |
| Between 0.6150 inches and 0.6350 inches  |                 |
| Flange Width:  |                 |
| Between 0.0570 inches and 0.0620 inches  |                 |
| Corner Shape:  |                 |
| Undercut left flange body corner   |                 |
| Material:  |                 |
| Steel comp 630 or steel comp xm-12   |                 |
| Material Specification:  |                 |
| Ams 5643 assn standard 1st material response or ams 5659 assn standard 2nd mat | terial response |
| Surface Treatment:   |                 |
| Passivate  |                 |
| Surface Treatment Specification:   |                 |
| Qq-p-35 federal specification single treatment response                        |                 |
| Style Designator:  |                 |
| 22c solid, external flange one end   |                 |
| Shelf Life:  |                 |
| N/a  |                 |
| Unit Of Measure:   |                 |
|  |                 |
| Demilitarization:  |                 |
| No   |                 |
| Fiig:  |                 |
| A045a0   |                 |