

View Online at <https://aerobasegroup.com/nsn/3120-01-015-5822>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Shank Style:**

Internally threaded w/bead and wrench flats

**Overall Length:**

Between 1.6720 inches and 1.7020 inches

**Bore Diameter:**

Between 0.2500 inches and 0.2505 inches

**Outer Member Outside Diameter:**

Between 0.7400 inches and 0.7600 inches

**Bore Center To Shank End Distance:**

Between 1.3020 inches and 1.3220 inches

**Outer Member Width:**

Between 0.2760 inches and 0.2860 inches

**Inner Member Width:**

Between 0.3700 inches and 0.3750 inches

**Shank Thread Length:**

Between 0.7188 inches and 0.8125 inches

**Shank Width Across Wrench Flats:**

0.3750 inches

**Static Radial Load Rating:**

5400 pounds

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Hardness Rating:**

60.0 rockwell c inner member and 63.0 rockwell c inner member

**Special Features:**

Fit-up 0.0005 in. Min 2.0000 in. Maximum oz

**Material:**

Steel comp e52100 inner member

**Surface Treatment:**

Cadmium rod end body

**Style Designator:**

Ball type

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A045a0