

View Online at <https://aerobasegroup.com/nsn/3120-01-015-5822>

Thread Class:

3b

Thread Direction:

Right-hand

Shank Style:

Internally threaded w/bead and wrench flats

Overall Length:

Between 1.6720 inches and 1.7020 inches

Bore Diameter:

Between 0.2500 inches and 0.2505 inches

Outer Member Outside Diameter:

Between 0.7400 inches and 0.7600 inches

Bore Center To Shank End Distance:

Between 1.3020 inches and 1.3220 inches

Outer Member Width:

Between 0.2760 inches and 0.2860 inches

Inner Member Width:

Between 0.3700 inches and 0.3750 inches

Shank Thread Length:

Between 0.7188 inches and 0.8125 inches

Shank Width Across Wrench Flats:

0.3750 inches

Static Radial Load Rating:

5400 pounds

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Hardness Rating:

60.0 rockwell c inner member and 63.0 rockwell c inner member

Special Features:

Fit-up 0.0005 in. Min 2.0000 in. Maximum oz

Material:

Steel comp e52100 inner member

Surface Treatment:

Cadmium rod end body

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A045a0