## NSN 3120-01-016-7593

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-016-7593

Overa	II I 🗚	nath:	
Overa	и се	natn:	

Between 0.3869 inches and 0.3939 inches

**Body Outside Diameter:** 

Between 0.8760 inches and 0.8765 inches

**Body Inside Diameter:** 

Between 0.7338 inches and 0.7348 inches

Flange Outside Diameter:

Between 1.0520 inches and 1.0720 inches

Flange Width:

Between 0.0930 inches and 0.0940 inches

**Corner Shape:** 

Undercut left flange body corner

**Hardness Rating:** 

26.0 rockwell c and 33.0 rockwell c

**Surface Finish:** 

63.0 microinches inside diameter surface of body

Material:

Steel comp 4140 or steel comp 8740 or steel comp 4130

**Surface Treatment:** 

Cadmium

**Surface Treatment Specification:** 

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Style Designator:** 

22c solid, external flange one end

**Specification Data:** 

97449-20 manufacturers specification

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A045a0