

View Online at <https://aerobasegroup.com/nsn/3120-01-027-2045>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

Between 2.6725 inches and 2.7025 inches

Bore Diameter:

Between 0.4370 inches and 0.4375 inches

Outer Member Outside Diameter:

Between 1.1150 inches and 1.1350 inches

Bore Center To Shank End Distance:

Between 2.1150 inches and 2.1350 inches

Outer Member Width:

Between 0.4470 inches and 0.4570 inches

Inner Member Width:

Between 0.5570 inches and 0.5670 inches

Shank Thread Length:

Between 1.3450 inches and 1.4350 inches

Static Radial Load Rating:

10500 pounds

Thread Diameter:

0.438 inches

Thready Qty Per Inch (tpi):

20

Special Features:

Std nas559 keyway in shank, magnaflux inspected

Material:

Steel race insert

Surface Treatment:

Cadmium rod end body

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response rod end body

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A045a0