NSN 3120-01-029-8994

Sleeve Bushing - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/3120-01-029-8994 | |
|---|----|
| Overall Length: | |
| Between 0.5520 inches and 0.5670 inches | |
| Body Outside Diameter: | |
| Between 0.5006 inches and 0.5013 inches | |
| Body Inside Diameter: | |
| Between 0.3750 inches and 0.3765 inches | |
| Flange Outside Diameter: | |
| Between 0.6150 inches and 0.6350 inches | |
| Flange Width: | |
| Between 0.0570 inches and 0.0620 inches | |
| Corner Shape: | |
| Undercut left flange body corner | |
| Surface Finish: | |
| 100.0 microinches intermediate layer | |
| Material: | |
| Copper alloy 642 | |
| Material Specification: | |
| Qq-c-465 federal specification single material response | |
| Surface Treatment: | |
| Cadmium | |
| Surface Treatment Specification: | |
| Qq-p-416, type 2, cl 2 federal specification single treatment respons | se |
| Style Designator: | |
| 22c solid, external flange one end | |
| Specification Data: | |
| 80205-nas77 professional/industrial association standard | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |

A045a0