

View Online at <https://aerobasegroup.com/nsn/3120-01-043-7815>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Shank Style:**

Internally threaded w/bead and wrench flats and inspection hole

**Overall Length:**

Between 1.8445 inches and 1.8745 inches

**Bore Diameter:**

Between 0.2495 inches and 0.2515 inches

**Lubrication Material:**

Grease, mil-g-23827

**Outer Member Outside Diameter:**

Between 0.7710 inches and 0.7910 inches

**Bore Center To Shank End Distance:**

Between 1.4590 inches and 1.4790 inches

**Outer Member Width:**

Between 0.3320 inches and 0.3470 inches

**Inner Member Width:**

Between 0.4320 inches and 0.4370 inches

**Shank Thread Length:**

Between 0.7190 inches and 0.8120 inches

**Inspection Hole Center To End Distance:**

0.3750 inches

**Shank Width Across Wrench Flats:**

0.5000 inches

**Static Radial Load Rating:**

5500 pounds

**Thread Diameter:**

0.312 inches

**Features Provided:**

External lubrication fitting

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

57.0 rockwell c inner member and 61.0 rockwell c inner member

**Lubrication Feature:**

Perforation race insert

**Special Features:**

Plating on comp e52100 inner member only

**Material:**

Steel comp e52100 inner member or steel comp 440c inner member

**Surface Treatment:**

Cadmium rod end body

**Style Designator:**

Ball type

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0