## NSN 3120-01-054-6007

Rod End Plain Bearing - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/3120-01-054-6007



**Thread Class:** 3b **Thread Direction: Right-hand** Shank Style: Internally threaded w/inspection hole **Overall Length:** Between 1.8570 inches and 1.8870 inches **Bore Diameter:** Between 0.2495 inches and 0.2500 inches **Outer Member Outside Diameter:** Between 0.7960 inches and 0.8160 inches **Bore Center To Shank End Distance:** Between 1.4590 inches and 1.4690 inches **Outer Member Width:** Between 0.3320 inches and 0.3420 inches **Inner Member Width:** Between 0.4350 inches and 0.4370 inches Shank Thread Length: 0.7500 inches **Inspection Hole Center To End Distance:** 0.3745 inches Shank Width Across Wrench Flats: Between 0.4270 inches and 0.4390 inches **Static Radial Load Rating:** 3240 pounds **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 Hardness Rating: 39.0 rockwell c rod end body and 42.0 rockwell c rod end body Surface Treatment: Cadmium rod end body Surface Treatment Specification: Qq-p-416, type 1, cl 2 federal specification single treatment response rod end body **Style Designator:** Ball type **Thread Series Designator:** Unjf Shelf Life: N/a

## NSN 3120-01-054-6007

Rod End Plain Bearing - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A045a0

