

View Online at <https://aerobasegroup.com/nsn/3120-01-056-5139>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Shank Style:**

Internally threaded w/bead and wrench flats and inspection hole

**Overall Length:**

Between 1.7710 inches and 1.7910 inches

**Bore Diameter:**

Between 0.2495 inches and 0.2515 inches

**Outer Member Outside Diameter:**

Between 0.8020 inches and 0.8220 inches

**Bore Center To Shank End Distance:**

Between 1.3650 inches and 1.3850 inches

**Outer Member Width:**

Between 0.2990 inches and 0.3090 inches

**Inner Member Width:**

Between 0.4320 inches and 0.4370 inches

**Shank Thread Length:**

0.7500 inches

**Inspection Hole Center To End Distance:**

Between 0.3070 inches and 0.3170 inches

**Shank Width Across Wrench Flats:**

Between 0.3650 inches and 0.3850 inches

**Static Radial Load Rating:**

2948 pounds

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Hardness Rating:**

60.0 rockwell c inner member

**Criticality Code Justification:**

Spcl

**Special Features:**

As differentiated by material which must conform to ships parts control center special quality control provisions

**Surface Treatment:**

Cadmium rod end body

**Special Test Features:**

Special quality control testing

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 2 federal specification single treatment response rod end body

**Style Designator:**

Ball type

**Test Data Document:**

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A045a0