View Online at https://aerobasegroup.com/nsn/3120-01-059-1165

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

Between 2.3100 inches and 2.3400 inches

Bore Diameter:

Between 0.3120 inches and 0.3125 inches

Outer Member Outside Diameter:

Between 0.8900 inches and 0.9100 inches

Bore Center To Shank End Distance:

Between 1.8650 inches and 1.8850 inches

Outer Member Width:

Between 0.3220 inches and 0.3320 inches

Inner Member Width:

Between 0.4350 inches and 0.4370 inches

Shank Thread Length:

Between 1.1560 inches and 1.2180 inches

Static Radial Load Rating:

7180 pounds

Thread Diameter:

0.3750 inches

Thready Qty Per Inch (tpi):

24

Material:

Steel comp 630 race insert

Material Specification:

Ams 5643 assn standard single material response race insert

Surface Treatment:

Cadmium rod end body and chromate rod end body

Surface Treatment Specification:

Qq-p-416, type 2, class2 federal specification single treatment response rod end body

Style Designator:

Ball type

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0