

View Online at <https://aerobasegroup.com/nsn/3120-01-063-2055>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

2.3300 inches

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

Outer Member Outside Diameter:

0.8600 inches

Bore Center To Shank End Distance:

1.8800 inches

Outer Member Width:

Between 0.2350 inches and 0.2450 inches

Inner Member Width:

Between 0.3410 inches and 0.3430 inches

Shank Thread Length:

1.0400 inches

Thread Diameter:

0.6250 inches

Thready Qty Per Inch (tpi):

24

Special Features:

Shank is hollow with external keyway. Hollow is 0.3440 in. Diameter by 1.0000 in. Long. Keyway is 0.845 in. Deep by 0.130 in. Wide by 1.040 in. Long

Material:

Steel comp 4140

Material Specification:

Mil-s-5626, cond c, d, or e military specification single material response

Surface Treatment:

Paint rod end body

Surface Treatment Specification:

Qq-p-416 federal specification single treatment response inner member

Style Designator:

Ball type

Thread Series Designator:

Unjef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A045a0

Mil-std (military Standard):

Mil-s-5626 spec.