

View Online at <https://aerobasegroup.com/nsn/3120-01-063-2055>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Style:**

Externally threaded

**Overall Length:**

2.3300 inches

**Bore Diameter:**

Between 0.2495 inches and 0.2500 inches

**Outer Member Outside Diameter:**

0.8600 inches

**Bore Center To Shank End Distance:**

1.8800 inches

**Outer Member Width:**

Between 0.2350 inches and 0.2450 inches

**Inner Member Width:**

Between 0.3410 inches and 0.3430 inches

**Shank Thread Length:**

1.0400 inches

**Thread Diameter:**

0.6250 inches

**Thready Qty Per Inch (tpi):**

24

**Special Features:**

Shank is hollow with external keyway. Hollow is 0.3440 in. Diameter by 1.0000 in. Long. Keyway is 0.845 in. Deep by 0.130 in. Wide by 1.040 in. Long

**Material:**

Steel comp 4140

**Material Specification:**

Mil-s-5626, cond c, d, or e military specification single material response

**Surface Treatment:**

Paint rod end body

**Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response inner member

**Style Designator:**

Ball type

**Thread Series Designator:**

Unjef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A045a0

**Mil-std (military Standard):**

Mil-s-5626 spec.