# NSN 3120-01-087-7062

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-087-7062

# **Overall Length:**

Between 0.2020 inches and 0.2170 inches

### **Body Outside Diameter:**

Between 0.6257 inches and 0.6265 inches

# **Body Inside Diameter:**

Between 0.5000 inches and 0.5015 inches

# Flange Outside Diameter:

Between 0.7400 inches and 0.7600 inches

#### Flange Width:

Between 0.0570 inches and 0.0620 inches

# Corner Shape:

Undercut left flange body corner

#### Surface Finish:

100.0 microinches intermediate layer

#### Material:

Steel comp 8630 or steel comp 4130

# **Material Specification:**

Mil-s-6050 military specification 1st material response or mil-s-6758 military specification 2nd material response

### Surface Treatment:

Cadmium

# Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

# Style Designator:

22c solid, external flange one end

#### **Specification Data:**

80205-nas77 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

```
---
```

Demilitarization:

No

Fiig:

A045a0

# Mil-std (military Standard):

Mil-s-6050 spec.