

View Online at <https://aerobasegroup.com/nsn/3120-01-087-9969>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Shank Style:**

Internally threaded w/bead and wrench flats and inspection hole

**Overall Length:**

Between 1.7400 inches and 1.7600 inches

**Bore Diameter:**

Between 0.1895 inches and 0.1915 inches

**Outer Member Outside Diameter:**

0.7500 inches

**Bore Center To Shank End Distance:**

Between 1.3650 inches and 1.3850 inches

**Outer Member Width:**

Between 0.3230 inches and 0.3330 inches

**Inner Member Width:**

Between 0.4320 inches and 0.4370 inches

**Shank Thread Length:**

0.7500 inches

**Inspection Hole Center To End Distance:**

Between 0.3070 inches and 0.3170 inches

**Shank Width Across Wrench Flats:**

0.3750 inches

**Static Radial Load Rating:**

2848 pounds

**Thread Diameter:**

0.250 inches

**Features Provided:**

Flush lubrication fitting

**Thready Qty Per Inch (tpi):**

28

**Hardness Rating:**

60.0 rockwell c inner member

**Lubrication Feature:**

Groove race insert

**Material:**

Steel comp e50100 inner member or steel comp e51100 inner member or steel comp e52100 inner member

**Material Specification:**

Qq-n-35 federal specification single material response race insert

**Surface Treatment:**

Cadmium rod end body

**Surface Treatment Specification:**

Qq-p-416, cl b federal specification single treatment response rod end body

**Style Designator:**

Ball type

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0