View Online at https://aerobasegroup.com/nsn/3120-01-094-2263

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Style:**

Externally threaded

**Overall Length:**

3.3875 inches

**Bore Diameter:**

Between 0.6245 inches and 0.6250 inches

**Outer Member Outside Diameter:**

Between 1.5150 inches and 1.5350 inches

**Bore Center To Shank End Distance:**

Between 2.6150 inches and 2.6350 inches

**Outer Member Width:**

Between 0.5720 inches and 0.5820 inches

**Inner Member Width:**

Between 0.7480 inches and 0.7500 inches

**Shank Thread Length:**

Between 1.5310 inches and 1.5930 inches

**Static Radial Load Rating:**

21900 pounds

**Thread Diameter:**

0.625 inches

**Thready Qty Per Inch (tpi):**

18

**Hardness Rating:**

55.0 rockwell c  inner member and 62.0 rockwell c  inner member

**Material:**

Steel comp 630 race insert

**Surface Treatment:**

Cadmium rod end body and chromate rod end body

**Style Designator:**

Ball type

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0