NSN 3120-01-094-2264

Rod End Plain Bearing - Page 1 of 2



Thread Class: 3a **Thread Direction:** Left-hand Shank Style: Externally threaded **Overall Length:** 3.3875 inches **Bore Diameter:** Between 0.6245 inches and 0.6250 inches **Outer Member Outside Diameter:** Between 1.5150 inches and 1.5350 inches **Bore Center To Shank End Distance:** Between 2.6150 inches and 2.6350 inches **Outer Member Width:** Between 0.5720 inches and 0.5820 inches **Inner Member Width:** Between 0.7480 inches and 0.7500 inches Shank Thread Length: Between 1.5310 inches and 1.5930 inches **Static Radial Load Rating:** 21900 pounds **Thread Diameter:** 0.625 inches Thready Qty Per Inch (tpi): 18 Hardness Rating: 55.0 rockwell c inner member and 62.0 rockwell c inner member Material: Steel comp 630 race insert Surface Treatment: Cadmium rod end body and chromate rod end body **Style Designator:** Ball type **Thread Series Designator:** Unf Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No



NSN 3120-01-094-2264

Rod End Plain Bearing - Page 2 of 2

Fiig: A045a0

