## NSN 3120-01-100-2679

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-100-2679

| 1.2700 inches  Body Outside Diameter:  Between 0.7500 inches and 0.7510 inches  Body Inside Diameter:  Between 0.6150 inches and 0.6210 inches  Corner Shape:  Square all corners  Surface Finish:  125.0 microinches |
|---|
| Between 0.7500 inches and 0.7510 inches  Body Inside Diameter:  Between 0.6150 inches and 0.6210 inches  Corner Shape:  Square all corners  Surface Finish:   |
| Body Inside Diameter:  Between 0.6150 inches and 0.6210 inches  Corner Shape:  Square all corners  Surface Finish:  |
| Between 0.6150 inches and 0.6210 inches  Corner Shape:  Square all corners  Surface Finish:   |
| Corner Shape: Square all corners Surface Finish:  |
| Square all corners  Surface Finish:   |
| Surface Finish:   |
|   |
| 125.0 microinches   |
|   |
| Special Features:   |
| Used on the b-52 acft   |
| Material:   |
| Steel comp 4130   |
| Material Specification:   |
| Mil-t-6736, type 1 military specification single material response  |
| Surface Treatment:  |
| Cadmium   |
| Surface Treatment Specification:  |
| Qq-p-416, class 3, type 1 federal specification single treatment response   |
| Style Designator:   |
| 17c solid, plain, no outside flanges  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A045a0  |
| Mil-std (military Standard):  |
| Mil-t-6736 spec.  |
|   |