## NSN 3120-01-100-8413

Sleeve Bushing - Page 1 of 1

**Demilitarization:** 

No Fiig: A045a0



View Online at https://aerobasegroup.com/nsn/3120-01-100-8413 **Overall Length:** Between 0.3600 inches and 0.3800 inches **Body Outside Diameter:** Between 0.7660 inches and 0.7670 inches **Body Inside Diameter:** Between 0.5015 inches and 0.5020 inches **Corner Shape:** Square all corners Hardness Rating: 34.0 rockwell c and 38.0 rockwell c **Surface Finish:** 63.0 microinches inside diameter surface of body **Special Features:** Liner od of body and right side of flange bonding agent and liner shallnot be affected by mil-h-5606/mil-h-83282 hydraulic fluid Stainless steel inner layer **Material Specification:** 77272414ds120-1 mfr ref single material response **Surface Treatment:** Passivate intermediate layer **Surface Treatment Specification:** 812055751 mfr ref single treatment response intermediate layer **Style Designator:** 17c solid, plain, no outside flanges **Test Data Document:** 81205-bac-5424 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a **Unit Of Measure:**