

View Online at <https://aerobasegroup.com/nsn/3120-01-103-3904>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Shank Style:**

Internally threaded w/hexagon end and inspection hole

**Overall Length:**

1.7650 inches

**Bore Diameter:**

Between 0.1895 inches and 0.1900 inches

**Outer Member Outside Diameter:**

Between 0.7710 inches and 0.7910 inches

**Bore Center To Shank End Distance:**

Between 1.3650 inches and 1.3850 inches

**Outer Member Width:**

Between 0.3320 inches and 0.3420 inches

**Inner Member Width:**

Between 0.4320 inches and 0.4370 inches

**Shank Thread Length:**

Between 0.7187 inches and 0.8125 inches

**Inspection Hole Center To End Distance:**

0.3125 inches

**Shank Width Across Wrench Flats:**

Between 0.4270 inches and 0.4390 inches

**Static Radial Load Rating:**

3600 pounds

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Material:**

Steel rod end body

**Material Specification:**

Dyflon, fscm 81376 mfr ref single material response race liner

**Surface Treatment:**

Cadmium rod end body

**Style Designator:**

Ball type

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A045a0