## NSN 3120-01-113-0645

Sleeve Bushing - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/3120-01-113-0645  |
|--|
| Overall Length:  |
| Between 0.1400 inches and 0.1500 inches  |
| Body Outside Diameter:   |
| Between 0.3131 inches and 0.3136 inches  |
| Body Inside Diameter:  |
| Between 0.1790 inches and 0.1840 inches  |
| Flange Outside Diameter:   |
| Between 0.4270 inches and 0.4470 inches  |
| Flange Width:  |
| Between 0.0550 inches and 0.0600 inches  |
| Corner Shape:  |
| Undercut left flange body corner   |
| Material:  |
| Steel comp 8630 or steel comp 4130   |
| Material Specification:  |
| Mil-s-6050 military specification 1st material response or mil-s-6758 military specification 2nd material response |
| Surface Treatment:   |
| Cadmium  |
| Surface Treatment Specification:   |
| Qq-p-416, type 2, cl 2 federal specification single treatment response   |
| Style Designator:  |
| 22c solid, external flange one end   |
| Specification Data:  |
| 80205-nas538 professional/industrial association standard  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A045a0   |

Mil-std (military Standard):

Mil-s-6050 spec.