## NSN 3120-01-116-0887

Rod End Plain Bearing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3120-01-116-0887

Thread Class: 3a Thread Direction: Right-hand Shank Style: Externally threaded Overall Length: Between 4.9200 inches and 4.9300 inches Bore Diameter: Between 0.7495 inches and 0.7500 inches Outer Member Outside Diameter: Between 2.3400 inches and 2.3600 inches Bore Center To Shank End Distance: 3.7500 inches Outer Member Width: Between 0.7920 inches and 0.8020 inches Inner Member Width: Between 0.9950 inches and 1.0000 inches Shank Thread Length: Between 1.7110 inches and 1.7260 inches Thread Diameter: 0.875 inches Thread Diameter: 14	
Tread Direction:Right-handShank Style:Externally threadedOverall Length:Between 4.9200 inches and 4.9300 inchesBore Diameter:Between 0.7495 inches and 0.7500 inchesOuter Member Outside Diameter:Between 2.3400 inches and 2.3600 inchesBore Center To Shank End Distance:3.7500 inchesOuter Member Width:Between 0.7920 inches and 0.8020 inchesBetween 0.7920 inches and 0.8020 inchesBetween 1.7110 inches and 1.260 inchesShank Thread Length:Between 1.7110 inches and 1.7260 inchesThread Diameter:0.875 inches1.7110 inches and 1.7260 inchesThread Length:1.7110 inches and 1.7260 inches1.7110 in	
Right-hand         Shank Style:         Externally threaded         Overall Length:         Between 4.9200 inches and 4.9300 inches         Bore Diameter:         Between 0.7495 inches and 0.7500 inches         Outer Member Outside Diameter:         Between 2.3400 inches and 2.3600 inches         Bore Center To Shank End Distance:         3.7500 inches         Outer Member Width:         Between 0.7920 inches and 0.8020 inches         Inner Member Width:         Between 1.7110 inches and 1.0000 inches         Hored Length:         0.875 inches         Thread Length:         0.875 inches         1.7110 inches and 1.7260 inches	
Shak Style:Externally threadedOverall Length:Between 4.9200 inches and 4.9300 inchesBore Diameter:Between 0.7495 inches and 0.7500 inchesOuter Member Outside Diameter:Between 2.3400 inches and 2.3600 inchesBore Center To Shank End Distance:3.7500 inchesOuter Member Width:Between 0.7920 inches and 0.8020 inchesBetween 0.7920 inches and 1.0000 inchesShak Thread Length:Between 1.7110 inches and 1.7260 inchesThread Diameter:0.875 inches112124	
Externally threadedOverall Length:Between 4.9200 inches and 4.9300 inchesBore Diameter:Between 0.7495 inches and 0.7500 inchesOuter Member Outside Diameter:Between 2.3400 inches and 2.3600 inchesBore Center To Shank End Distance:3.7500 inchesOuter Member Width:Between 0.7920 inches and 0.8020 inchesBetween 0.9950 inches and 1.0000 inchesShank Thread Length:Between 1.7110 inches and 1.7260 inchesThread Diameter:0.875 inches11Between 1.7110 inches and 1.7260 inches1114	
Overall Length:Between 4.9200 inches and 4.9300 inchesBore Diameter:Between 0.7495 inches and 0.7500 inchesOuter Member Outside Diameter:Between 2.3400 inches and 2.3600 inchesBore Center To Shank End Distance:3.7500 inchesOuter Member Width:Between 0.7920 inches and 0.8020 inchesInner Member Width:Between 0.9950 inches and 1.0000 inchesShank Thread Length:Between 1.7110 inches and 1.7260 inchesThread Diameter:0.875 inches11Thread Vid Per Inch (tpi):14	
Between 4.9200 inches and 4.9300 inchesBore Diameter:Between 0.7495 inches and 0.7500 inchesOuter Member Outside Diameter:Between 2.3400 inches and 2.3600 inchesBore Center To Shank End Distance:3.7500 inchesOuter Member Width:Between 0.7920 inches and 0.8020 inchesInner Member Width:Between 0.9950 inches and 1.0000 inchesShank Thread Length:Between 1.7110 inches and 1.7260 inchesThread Diameter:0.875 inchesThread Vid Y Per Inch (tpi):14	
Between 0.7495 inches and 0.7500 inchesOuter Member Outside Diameter:Between 2.3400 inches and 2.3600 inchesBore Center To Shank End Distance:3.7500 inchesOuter Member Width:Between 0.7920 inches and 0.8020 inchesInner Member Width:Between 0.9950 inches and 1.0000 inchesShank Thread Length:Between 1.7110 inches and 1.7260 inchesThread Diameter:0.875 inches14	
Outer Member Outside Diameter:Between 2.3400 inches and 2.3600 inchesBore Center To Shank End Distance:3.7500 inchesOuter Member Width:Between 0.7920 inches and 0.8020 inchesInner Member Width:Between 0.9950 inches and 1.0000 inchesShank Thread Length:Between 1.7110 inches and 1.7260 inchesInread Diameter:0.875 inchesInread Y Diameter:14	
Between 2.3400 inches and 2.3600 inchesBore Center To Shank End Distance:3.7500 inchesOuter Member Width:Between 0.7920 inches and 0.8020 inchesInner Member Width:Between 0.9950 inches and 1.0000 inchesShank Thread Length:Between 1.7110 inches and 1.7260 inchesThread Diameter:0.875 inchesThready Qty Per Inch (tpi):14	
Bore Center To Shank End Distance:3.7500 inchesOuter Member Width:Between 0.7920 inches and 0.8020 inchesInner Member Width:Between 0.9950 inches and 1.0000 inchesShank Thread Length:Between 1.7110 inches and 1.7260 inchesThread Diameter:0.875 inchesThready Qty Per Inch (tpi):14	
3.7500 inchesOuter Member Width:Between 0.7920 inches and 0.8020 inchesInner Member Width:Between 0.9950 inches and 1.0000 inchesShank Thread Length:Between 1.7110 inches and 1.7260 inchesThread Diameter:0.875 inchesThready Qty Per Inch (tpi):14	
Outer Member Width:Between 0.7920 inches and 0.8020 inchesInner Member Width:Between 0.9950 inches and 1.0000 inchesShank Thread Length:Between 1.7110 inches and 1.7260 inchesThread Diameter:0.875 inchesThready Qty Per Inch (tpi):14	
Between 0.7920 inches and 0.8020 inches Inner Member Width: Between 0.9950 inches and 1.0000 inches Shank Thread Length: Between 1.7110 inches and 1.7260 inches Thread Diameter: 0.875 inches Thready Qty Per Inch (tpi): 14	
Inner Member Width: Between 0.9950 inches and 1.0000 inches Shank Thread Length: Between 1.7110 inches and 1.7260 inches Thread Diameter: 0.875 inches Thready Qty Per Inch (tpi):	
Between 0.9950 inches and 1.0000 inches Shank Thread Length: Between 1.7110 inches and 1.7260 inches Thread Diameter: 0.875 inches Thready Qty Per Inch (tpi): 14	
Shank Thread Length:Between 1.7110 inches and 1.7260 inchesThread Diameter:0.875 inchesThready Qty Per Inch (tpi):14	
Between 1.7110 inches and 1.7260 inches Thread Diameter: 0.875 inches Thready Qty Per Inch (tpi): 14	
Thread Diameter: 0.875 inches Thready Qty Per Inch (tpi): 14	
0.875 inches Thready Qty Per Inch (tpi): 14	
Thready Qty Per Inch (tpi): 14	
14	
Hardness Rating:	
56.0 rockwell c rod end body and 30.0 rockwell c rod end body and 34.0 rockwell c rod end body and 38.0 rockwell c rod end l	ody
Special Features:	
Sq keyway on shank 0.3200 in. W	
Material:	
Steel rod end body	
Material Specification:	
Ams 5659 15-5ph assn standard single material response rod end body	
Surface Treatment:	
Passivate rod end body	
Surface Treatment Specification:	
Bac5751, 81205 mfr ref single treatment response rod end body	
Style Designator:	
Ball type	
Thread Series Designator:	
Unjf	
Shelf Life:	
N/a	

## NSN 3120-01-116-0887

Rod End Plain Bearing - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A045a0

