

View Online at <https://aerobasegroup.com/nsn/3120-01-117-2443>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Shank Style:**

Internally threaded w/bead and wrench flats and inspection hole

**Overall Length:**

2.1250 inches

**Bore Diameter:**

Between 0.3745 inches and 0.3765 inches

**Outer Member Outside Diameter:**

Between 0.9900 inches and 1.0100 inches

**Bore Center To Shank End Distance:**

Between 1.6150 inches and 1.6350 inches

**Outer Member Width:**

Between 0.4010 inches and 0.4110 inches

**Inner Member Width:**

Between 0.4950 inches and 0.5000 inches

**Shank Thread Length:**

0.9370 inches

**Inspection Hole Center To End Distance:**

Between 0.4640 inches and 0.4740 inches

**Shank Width Across Wrench Flats:**

Between 0.5520 inches and 0.5720 inches

**Static Radial Load Rating:**

9575 pounds

**Thread Diameter:**

0.375 inches

**Features Provided:**

External lubrication fitting

**Thready Qty Per Inch (tpi):**

24

**Special Features:**

0.0002 in. Min, 0.0005 in. Maximum radial play

**Material:**

Steel inner member

**Surface Treatment:**

Cadmium rod end body

**Style Designator:**

Ball type

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0